

<b>File Dynamics</b> 14-Jan-10 10:45 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN <del>KIPS</del> 0.1 FR 20000 MB 30  DL -41 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1000	FS 10 BN 68 SL 2839/ 3440/ 99  PJ: sn PN: HOPBAR  TG F2 -- US A2 F2 3.3   TS 12 TB 8.0 B PD: 10869-060 T1 9.2 2L/C 4.7 UA 1000 UE 1022 LP 0.00 ft LI 1.0
---	--

ACCEPT SQ-OFF FL-OFF PR-OFF  
 UMX= 4.0 FMX= 63 AMX= 110  
 EMX= 0.2 MEX= 123 FUP= 0.99



contact File Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 10869  
 CALIBRATION FACTOR: 1000 G/v  
 PAK (\*5000)\* DATE: 14-Jan-10  
 PDA OPERATOR: Dale B. *Bennell*