

<b>Pile Dynamics</b> 24-Feb-04 14:57		FS — 10	BN 197 SL 2498 / 3440 / 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN <del>KIPS/ft</del> FR 20000 MB 30					
DL -43 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1020	TS 12 TB 8.0	E B PD: 10870 T1 9.7 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0	

<input type="checkbox"/> ACCEPT <input type="checkbox"/> SQ-OFF <input type="checkbox"/> FL-OFF <input type="checkbox"/> PR-OFF	UMX = 4.8 FMX = 74 AMX = 179 EMX = 0.3 MEX = 145 FUP = 1.00
--	--



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 10870  
 CALIBRATION FACTOR: 1020 G/V  
 PAK < \*5000 > : \_\_\_\_\_ DATE: 24-Feb-04  
 PDA OPERATOR: Fred Hussein

<-AT:PIEZORESISTIVE

OP: fred [ver:4.05]

AT:PIEZOELECTRIC->