

<b>Pile Dynamics</b> 24-Feb-04 14:54		FS — 10	BN 193 SL 2496/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN <del>KIPS/ft</del> FR 20000 MB 30	DL -39 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 997	TS 12 TB 8.0	E B PD: 10871 T1 9.6 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF  
 UMX= 4.5 FMX= 70 AMX= 159  
 EMX= 0.3 MEX= 137 FUP= 1.00



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 10871  
 CALIBRATION FACTOR: 997 G/V  
 ROK (x5000): \_\_\_\_\_ DATE: 24-Feb-04  
 PDA OPERATOR: Fred Muscin