

File Dynamics 15-Dec-05 18:37 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1010	FS — BN 222 10 SL 2517/ 3440/ 2 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3	
TS 12 TB 7.0	B PD: 11035-060 T1 9.5 2L/C 4.7 VA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.4 FMX= 68 AMX= 159
 EMX= 0.3 MEX= 133 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11035

CALIBRATION FACTOR: 1010 G/V

PAK (*5000): _____ DATE: 15-Dec-05

PDA OPERATOR: *Fred Hamer*