

Pile Dynamics 03-May-04 12:53		FS 10 BN 262 SL 2543/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30	DL -41 UT -1 PK 1 TM-PEAK			
F1 500 F2 213 A1 999 A2 1030	TS 12 TB 8.0	B PD: 11069 T1 9.2 2L/C 4.7	UA 1000 UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 3.6 FMX= 56 AMX= 80
 EMX= 0.2 MEX= 109 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11069
 CALIBRATION FACTOR: 1030 GIV
 PAK (*5000): _____ DATE: 03-May-04
 PDA OPERATOR: Fred Hussein