

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 03-May-04 12:46		FS — 10	BN 252 SL 2543/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 E2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPSE0.1 FR 20000 MB 30 DL -40 VT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 980	TS 12 TB 8.0	B PD: 11072 T1 9.2 2L/C 4.7	UA 1000 UE 1022	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 3.5 FMX= 56 AMX= 80
 EMX= 0.2 MEX= 109 FUP= 1.00

	ACCELEROMETER CALIBRATION N.I.S.T. Traceable
	SERIAL NUMBER: 11072 CALIBRATION FACTOR: 980 G/V PAK (*3000): _____ DATE: 03-May-04 PDA OPERATOR: Fred Huessein

contact Pile Dynamics USA with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916
 OP: FRED [ver:4.05]

<-AT:PIEZORESISTIVE >AT:PIEZOELECTRIC>