

<b>File Dynamics</b> <b>28-May-04 09:36</b> LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN <del>KIPS:0</del> FR 20000 MB 30  DL -40 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1020	FS — 10  BN 616 SL 2573/ 3440/ 2  PJ: PN: HOPBAR  TG F2 -- US A2 F2 3.3  TS 12 B PD: 11146 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 <b>UE 1024</b> LI 1.0
--	---

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.4 FMX= 68 AMX= 139 EMX= 0.3 MEX= 133 FUP= 1.01
-----------------------------	--

contact File Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11146

CALIBRATION FACTOR: 1020 G/V

PAK (~~\*5888~~): \_\_\_\_\_ DATE: 28-May-04

PDA OPERATOR: Fred Unzueta