

Pile Dynamics 28-May-04 09:31 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30 DL -32 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1015	FS — BN 612 10 SL 2571/ 3440/ 2 PJ: PN: HOPBAR TG F2 -- US A2 E2 3.3 TS 12 B PD: 11147 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1024 LI 1.0
---	--

UMX= 4.6 FMX= 71 AMX= 149
 EMX= 0.3 MEX= 139 FVP= 1.00

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11147
 CALIBRATION FACTOR: 1015 G/V
 PAK <←5000>: _____ DATE: 28-May-04
 PDA OPERATOR: Fred Hussein

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

>AT:PIEZOELECTRIC->