

File Dynamics 14-Mar-05 09:28 LE 39.6 ft AR 1.7 in <sup>2</sup> EM 30000 Ksi SP 0.492 K/ft <sup>3</sup> WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN <del>KIPS</del> 0.1 FR 20000 MB 30  DL -40 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1015	FS — 10	BN 113 SL 2508 / 3440 / 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------	-------------------------------	-------------------	--------------------------

TS 12	B PD: 11152-060	LP 0.00 ft	FF-2
TB 8.0	T1 9.6 2L/C 4.7 UA 1000	UE 1022	LI 1.0 UF-2

ACCEPT SQ-OFF FL-OFF PR-OFF  
 UMX= 4.9 FMX= 77 AMX= 169  
 EMX= 0.4 MEX= 150 FVP= 0.99



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 11152  
 CALIBRATION FACTOR: 1015 G/V  
 PAK (\*5080): \_\_\_\_\_ DATE: 14-MV-05  
 PDA OPERATOR: Fred Hudec