

Pile Dynamics 06-Jul-04 07:55		FS — 10	BN 355 SL 2564/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS/FT FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1045					
TS 12 B PD: 11166 LP 0.00 ft TB 7.0 T1 9.6 2L/C 4.7 UA 1000 UE 1024 LI 1.0					

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.7 FMX= 72 AMX= 169
 EMX= 0.3 MEX= 141 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11166

CALIBRATION FACTOR: 1045 G/V

PAK ~~(#5000)~~: _____ DATE: 06-Jul-04

PDA OPERATOR: Fred Johnson

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->