

<b>Pile Dynamics</b> 06-Jul-04 07:58		FS — 10	BN 360 SL 2564/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN <del>KIPSSD</del> FR 20000 MB 30  DL -42 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1080					
		TS 12 TB 7.0	B PD: 11167 T1 9.6 2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF  
 UMX= 5.2 FMX= 80 AMX= 179  
 EMX= 0.4 MEX= 156 FUP= 1.00



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 11167  
 CALIBRATION FACTOR: 1080 G/V  
 PAK (\*5800): \_\_\_\_\_ DATE: 06-JUL-04  
 PDA OPERATOR: *Fred Huszari*

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->