

File Dynamics 17-Nov-05 21:26 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS 30.1 FR 20000 MB 30 DL -39 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1035	FS — BN 760 10 SL 2559/ 3440/ 99 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 11256-060 LP 0.00 ft TB 7.0 Tl 9.6 2L/C 4.7 UA 1000 VE 1022 LI 1.0
--	--

ACCEPT SQ-OFF FL-OFF PR-OFF contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.5 FMX= 69 AMX= 189 EMX= 0.3 MEX= 135 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11256 CALIBRATION FACTOR: 1035 G/V PAK (45000) : _____ DATE: 17-Nov-05 PDA OPERATOR: <i>Fred</i>
--	---

←-AT:PIEZORESISTIVE OP: FRED [ver:4.05] AT:PIEZOELECTRIC->