

| | | |
|--|---|--|
| File Dynamics 06-Aug-08 08:41 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS=0 FR 20000 MB 30 DL -39 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1030 | FS 10 BN 234 SL 2776/ 3440/ 2 PJ: sn PN: HOPBAR T6 F2 -- US A2 F2 3.3 TS 12 TB 7.0 T1 9.5 B PD: 11265-60 2L/C 4.7 VA 1000 LP 0.00 ft LI 1.0 | |
|--|---|--|

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.6 FMX= 71 AMX= 179
 EMX= 0.3 MEX= 139 FVP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11265

CALIBRATION FACTOR: 1030 G/V

PAK (<5000): _____ DATE: 6 Aug 08

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: DAVE [ver:4.05]

AT:PIEZOELECTRIC->