

File Dynamics 05-Jun-09 05:19	FS — 10	BN 63 SL 2751/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -34 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 990						
TS 12 TB 7.0					B PD: 11278-060 T1 9.6 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0
VE 1022						
E1						
ACCEPT SQ-OFF FL-OFF PR-OFF						

<p>UMX= 4.2 FMX= 66 AMX= 159 EMX= 0.3 MEX= 129 FUP= 1.00</p> <p>ACCELEROMETER CALIBRATION N.I.S.T. Traceable</p> <p>SERIAL NUMBER: 11278</p> <p>CALIBRATION FACTOR: 990 G/v</p> <p>PAK (*5800) DATE: 5-JUN-09</p> <p>PDA OPERATOR: Dale Burrell</p>
<p>contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>
<p>←-AT:PIEZORESISTIVE OP: dale [ver:4.05] AT:PIEZOELECTRIC-></p>