

Pile Dynamics 23-Jun-05 10:08 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN 16810 FR 20000 MB 30 DL -39 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1010	FS 10 BN 797 SL 2585/ 3440/ 99 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3
TS 12 TB 8.0	B PD: 11282-060 T1 9.6 2L/C 4.7 UA 1000 LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.8 FMX= 74 AMX= 169
 EMX= 0.3 MEX= 145 FUP= 0.99

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11282

CALIBRATION FACTOR: 1010 G/V

PAK (<5000>): _____ DATE: 23-Jun-05

PDA OPERATOR: Fred Hanis