

File Dynamics 26-May-04 13:57	FS — 10	BN 344 SL 2544/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN 31530 ft FR 20000 MB 30				
DL -42 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1060				
TS 12 B PD: 11283 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 VE 1024 LI 1.0				

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.4 FMX= 68 AMX= 169  
EMX= 0.3 MEX= 133 FUP= 1.00

contact Pile Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11283

CALIBRATION FACTOR: 1060 G/V

PAK <#5000>: \_\_\_\_\_ DATE: 26-May-04

PDA OPERATOR: Fred Pharris