

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 09-Aug-04 10:01 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -38 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1048	FS — 10	BN 560 SL 2609/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
---	------------	-----------------------------	-------------------	--------------------------

TS 12	B PD: 11378	LP 0.00 ft	
TB 8.0	T1 9.6 2L/C 4.7	UA 1000	UE 1024 LI 1.0

ACCERT SQ-OFF FL-OFF PR-OFF
 VMX= 6.3 FMX= 97 AMX= 229
 EMX= 0.6 MEX= 190 FUP= 1.00

<p>contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>11378</u> CALIBRATION FACTOR: <u>1048 G/V</u> PAK (*5000): _____ DATE: <u>09-Aug-04</u> PDA OPERATOR: <u>Fred Hossin</u>
	←-AT:PIEZORESISTIVE OP: FRED [ver:4.05] AT:PIEZOELECTRIC ->