

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 09-Aug-04 09:57		FS — 10	BN 549 SL 2609 / 3440 / 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30	DL -39 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1050	TS 12 TB 8.0	B PD: 11380 T1 9.6	2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 5.7 FMX= 89 AMX= 189
 EMX= 0.5 MEX= 174 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11380
 CALIBRATION FACTOR: 1050 G/V
 PAK < *5000 > : _____ DATE: 09-Aug-04
 PDA OPERATOR: *Fred Hussein*

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->