

Pile Dynamics 30-Aug-04 11:03 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 990	FS — BN 113 SL 2493/ 3440/ 99 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3	
TS 12 TB 7.0	E B PD: 11383 T1 9.4 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0

UMX= 4.0 FMX= 63 AMX= 120
 EMX= 0.2 MEX= 123 FUP= 1.01

<p> contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916 </p>	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>11383</u> CALIBRATION FACTOR: <u>990 G/V</u> PAK (*5000): _____ DATE: <u>30 Aug 04</u> PDA OPERATOR: <u>[Signature]</u>
---	--