

| | | | | | |
|---|-----------------|-----------------------|-----------------------------|-------------------|--------------------------|
| Pile Dynamics 04-Aug-04 07:20 | | FS — 10 | BN 259 SL 2530/ 3440/ 99 | PJ: PN: HOPBAR | TG F2 -- US A2 F2 3.3 |
| LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 | | | | | |
| EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30 DL -39 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1078 | TS 12 TB 8.0 | B PD: 11394 T1 9.6 | 2L/C 4.7 UA 1000 | UE 1024 LI 1.0 | LP 0.00 ft LI 1.0 |

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 5.5 FMX= 86 AMX= 219
 EMX= 0.4 MEX= 168 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11394
 CALIBRATION FACTOR: 1078 G/V
 PAK ~~←#8888→~~: _____ DATE: 04-Aug-04
 PDA OPERATOR: Fred Hussein