

Pile Dynamics 30-Aug-04 11:07		FS — 10	BN 123 SL 2493/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30	DL -38 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1060	TS 12 TB 7.0	E B PD: 11396 T1 9.4 2L/C 4.7	UA 1000 UE 1022	LP 0.00 ft LI 1.0	

ACCERT SQ-OFF FL-OFF PR-OFF
 VMX= 3.8 FMX= 60 AMX= 120
 EMX= 0.2 MEX= 117 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11396
 CALIBRATION FACTOR: 10606/V
 PAK (*5000)* DATE: 30 Aug 04
 PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: Dave [ver:4.05]

AT:PIEZOELECTRIC->