

Pile Dynamics 28-Jul-04 14:19		FS — 10	BN 59 SL 2483/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS 20.1 FR 20000 MB 30	DL -38 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1040	TS 12 TB 8.0	E B PD: 11397 T1 9.6 2L/C 4.7	UA 1000	UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 5.1 FMX= 80 AMX= 179
 EMX= 0.4 MEX= 156 FVP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11397
 CALIBRATION FACTOR: 1040 G/V
 PAK (<5000>): _____ DATE: 28-JUL-04
 PDA OPERATOR: Fred Hussein

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->