

Pile Dynamics 02-Aug-04 15:17		FS 10 BN 233 SL 2525 / 3440 / 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS/ft FR 20000 MB 30 DL -35 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1038				
TS 12 TB 8.0		B PD: 11399 T1 9.6 2L/C 4.7 VA 1000		LP 0.00 ft LI 1.0

SQ-OFF FL-OFF PR-OFF
 UMX= 5.0 FMX= 78 AMX= 179
 EMX= 0.4 MEX= 152 FUP= 0.99



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11399
 CALIBRATION FACTOR: 1038 G/V
 PAK <(*5000)> : _____ DATE: 02-Aug-04
 PDA OPERATOR: Fred Huber