

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 02-Aug-04 15:07	FS —	BN 211	PJ:	TG F2 -- US
LE 39.6 ft	10	SL 2524/ 3440/ 2	PN: HOPBAR	A2 F2 3.3
AR 1.7 in2				
EM 30000 Ksi				
SP 0.492 K/ft3				
WS 16810 ft/s				
WC 16862 ft/s				
JC 0.40				
FM 1.00				
UM 1.00				
EA/C 30.3 Ks/ft				
UN KIPS*0.1				
FR 20000 MB 30	TS 12	B PD: 11401	LP 0.00 ft	
DL -31	TB 8.0	T1 9.6	2L/C 4.7	VA 1000
UT -1				UE 1024
PK 1 TM-PEAK				LI 1.0
F1 500				
F2 213				
A1 999				
A2 1050				

<input type="checkbox"/> ACCEPT	<input type="checkbox"/> SQ-OFF	<input type="checkbox"/> FL-OFF	<input type="checkbox"/> PR-OFF	VMX= 4.6 FMX= 72 AMX= 159 EMX= 0.3 MEX= 141 FVP= 1.00
				ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11401 CALIBRATION FACTOR: 1050 G/V BAK (*5000): _____ DATE: 02-Aug-04 PDA OPERATOR: Fred Krosch
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916				OP: FRED Iver:4.051

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->