

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 02-Aug-04 15:20		FS — BN 241 10 SL 2525/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30				
DL -41 UT -1 PK 1 TM-PEAK	TS 12 B PD: 11409 LP 0.00 ft TB 8.0 T1 9.7 2L/C 4.7 VA 1000 UE 1024 LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 5.2 FMX= 81 AMX= 189 FMX= 0.4 MEX= 158 FVP= 1.00
<p>contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11409 CALIBRATION FACTOR: 1010 G/V BAK (<5000>): _____ DATE: 02-Aug-04 PDA OPERATOR: Fred Nuccio
	<-AT:PIEZORESISTIVE OP: FRED Iver:4.05I AT:PIEZOELECTRIC->