

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 04-Aug-04 07:16	FS — 10	BN 248 SL 2529/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30							
DL -38 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1055							
TS 12 TB 8.0					B PD: 11411 T1 9.6 2L/C 4.7	VA 1000	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF							
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916							
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>11411</u> CALIBRATION FACTOR: <u>1055 G/V</u> PDA OPERATOR: <u>Fred Hussein</u> DATE: <u>04-Aug-04</u>							

UM~~X~~= 5.5 FMX= 85 AMX= 209
 EMX= 0.4 MEX= 166 FVP= 1.00
 OP: FRED [ver:4.051]

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->