

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 27-Apr-10 11:40	FS — 10	BN 2224 SL 3029/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3				
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s								
JC 0.40 FM 1.00 UM 1.00								
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30								
DL -27 UT -1 PK 1 TM-PEAK								
F1 500 F2 213 A1 999 A2 1030								
TS 12 TB 8.0					B PD: 11419-060 T1 9.6	2L/C 4.7 VA 1000	UE 1022	LP 0.00 ft LI 1.0

<p>contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	<p>UMX= 4.0 FMX= 62 AMX= 139 EMX= 0.2 MEX= 121 FVP= 0.99</p>
	<p>ACCEPT SQ-12 FL-OFF PR-OFF</p> <p>ACCELEROMETER CALIBRATION N.I.S.T. Traceable</p> <p>SERIAL NUMBER: 11419</p> <p>CALIBRATION FACTOR: 1030 G/v</p> <p>PAK (*5000): DATE: 27-APR-10</p> <p>PDA OPERATOR: <i>[Signature]</i></p>

<-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC->