

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics
2018-05-14 15:13
LE 17.0 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 7234 ft/s

FS — BN 2710
10 SL 1385/ 3440/ 99

PJ:
PN: HOPBAR

TG F2 -- US
A2 F2 3.3

JC 0.40
FM 1.00
UM 1.00

EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90

DL -39
UT -1 IP 0.00
PK 1 TM-PEAK


F1 500
F2 213
A1 999
A2 1065

TS 12 B PD: 11422-060 LP 0.00 ft
TB 8.0 T1 9.6 2L/C 4.7 VA 1000 UE 1024 LI 1.0

VMX= 4.9 FMX= 70 AMX= 149
EMX= 0.3 MEX= 137 FVP= 1.00

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11422

CALIBRATION FACTOR: 1065 g/v

PAK (*5000): DATE: 14 MAY 18

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: Iaine [ver:5.01]

AT:PIEZOELECTRIC->