

File Dynamics 09-Aug-04 08:15	FS — 10	BN 493 SL 2599/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN <del>KIPS:0.1</del> FR 20000 MB 30	TS 12 B PD: 11523 LP 0.00 ft TB 8.0 T1 9.3 2L/C 4.7 UA 1000 UE 1024 LI 1.0			
DL -38 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 995				

ACCEPT SQ-OFF FL-OFF PR-OFF  
 UMX= 4.4 FMX= 68 AMX= 110  
 EMX= 0.3 MEX= 133 FUP= 0.99



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 11523  
 CALIBRATION FACTOR: 995 G/V  
 PAK (\*3000): \_\_\_\_\_ DATE: 09-Aug-04  
 PDA OPERATOR: Fred Thacker