

<b>Pile Dynamics</b> 20-Feb-05 17:07		FS 10	BN 993 SL 2670/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30	DL -39 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1010	TS 12 TB 8.0	B PD: 11839-060 T1 9.5	2L/C 4.7 VA 1000	UE 1022	LP 0.00 ft LI 1.0

ACCER SQ-OFF FL-OFF PR-OFF  
 VMX= 4.7 FMX= 73 AMX= 159  
 EMX= 0.3 MEX= 143 FUP= 1.00

contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 11839  
 CALIBRATION FACTOR: 1010 G/V  
 PAK (<5000): DATE: 20-Feb-05  
 PDA OPERATOR: Fred Hussein  
 OP: FRED [ver:4.05]