


File Dynamics 14-Oct-04 09:03 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1010	FS — BN 78 10 SL 2491/ 3440/ 2 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 E B PD: 11851-060 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0
---	---

ACCEPT SQ-OFF FL-OFF PR-OFF  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	UMX= 4.6 FMX= 72 AMX= 149 EMX= 0.4 MEX= 141 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11851 CALIBRATION FACTOR: 1010 G/V PAK (*5000): _____ DATE: 14-Oct-04 PDA OPERATOR: Fred Johnson OP: FRED [ver:4.05]
--	---