

<b>Pile Dynamics</b> 11-Oct-04 13:51		FS — 10	BN 1354 SL 2741/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN <del>KIPS/IN</del> FR 20000 MB 30	DL -41 UT 0 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 775	TS 12 TB 8.0	B PD: 11853-060 T1 9.6 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.5 FMX= 70 AMX= 139  
 EMX= 0.3 MEX= 137 FUP= 1.00



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 11853  
 CALIBRATION FACTOR: 775 GIV  
 PAK (<3000>): \_\_\_\_\_ DATE: 11-Oct-04  
 PDA OPERATOR: Fred Hussein