

File Dynamics 18-Jan-10 10:45	FS — 10	BN 45 SL 2844/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN 4125 0.1 FR 20000 MB 30	TS 12 B PD: 11854-060 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 200 UE 1022 LI 1.0			
DL -42 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1035				

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.3 FMX= 66 AMX= 159
 EMX= 0.3 MEX= 129 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11854

CALIBRATION FACTOR: 1035 G/g

PAK (*5000) DATE: 18-Jan-10

PDA OPERATOR: Dale Barwell

<-AT:PIEZORESISTIVE

OP: date [ver:4.05]

AT:PIEZOELECTRIC->