

File Dynamics 01-Mar-08 11:46 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN <del>KIPS:30</del> FR 20000 MB 30  DL -27 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1040	FS 10 BN 474 SL 2770/ 3440/ 99  PJ: sn PN: HOPBAR  TG F2 -- US A2 F2 3.3  TS 12 B PD: 12546-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0
---	---

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 3.9 FMX= 60 AMX= 149  
 EMX= 0.2 MEX= 117 FUP= 1.00



contact File Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 12546

CALIBRATION FACTOR: 1040 61V

PAK (\*5000): DATE: 01-MAR-08

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->

