

Pile Dynamics 06-Aug-09 08:43		FS — 10	BN 54 SL 2795/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US 02 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS:0 FR 20000 MB 30	DL -29 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1040	TS 12 TB 8.0	B PD: 12547-060 T1 9.5 2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 3.9 FMX= 61 AMX= 139
 EMX= 0.2 MEX= 119 FVP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 12547
 CALIBRATION FACTOR: 1040 Gw
~~PAK (*5888):~~ DATE: 06-AUG-09
 PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->

