

File Dynamics 22-Oct-04 13:16 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30  DL -41 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1025	FS — BN 422 10 SL 2553/ 3440/ 99  PJ: PN: HOPBAR  T6 F2 -- US A2 F2 3.3	
TS 12 TB 7.0	B PD: 12548-060 T1 9.5 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF  
 VMX= 4.5 FMX= 70 AMX= 149  
 EMX= 0.3 MEX= 137 FUP= 0.99



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 12548  
 CALIBRATION FACTOR: 1025 G/V  
 PAK ← \*50007: \_\_\_\_\_ DATE: 22-Oct-04  
 PDA OPERATOR: Fred Huszari