

<b>File Dynamics</b> 28-Oct-04 12:02 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN <del>KIPSSQ</del> FR 20000 MB 30  DL -40 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1035	FS 10 BN 174 SL 2523/ 3440/ 99  PJ: PN: HOPBAR  TG F2 -- US A2 F2 3.3  TS 12 B PD: 12549-060 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 <b>UE-1022</b> LI 1.0
---	--

**ACCEPT** SQ-OFF FL-OFF PR-OFF  
 VMX= 4.9 FMX= 76 AMX= 169  
 EMX= 0.4 MEX= 149 FVP= 1.01



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 12549  
 CALIBRATION FACTOR: 1035 G/V  
 PAK (\*3000): \_\_\_\_\_ DATE: 28-Oct-04  
 PDA OPERATOR: Fred Hansen