

Pile Dynamics 20-Jul-11 14:17 LE 39.6 ft AR 1.7 in ² EM 30000 Ksi SP 0.492 K/ft ³ WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS:30.1 FR 20000 MB 30 DL -29 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1075	FS — BN 138 10 SL 3192/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 13541-060 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1022 LI 1.0
--	--

ACCEPT SQ-OFF FL-OFF PR-OFF contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.0 FMX= 62 AMX= 159 EMX= 0.2 MEX= 121 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 13541 CALIBRATION FACTOR: 1075 G/v PAK (*5000): DATE: 21-JUL-11 PDA OPERATOR: <i>[Signature]</i>
---	--

<-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC->