

Pile Dynamics 11-Jul-12 12:37	FS — 10	BN 1363 SL 119/ 3440/ 4	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30 DL -28 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1020				
TS 12 TB 8.0		B PD: 14772-060 T1 9.5 2L/C 4.7 UA 1000		LP 0.00 ft LI 1.0

~~ACCEPT~~ SQ-OFF FL-OFF PR-OFF
 VMX= 4.0 FMX= 62 AMX= 139
 EMX= 0.2 MEX= 121 FUP= 0.99

<p> contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916 </p>	ACCELEROMETER CALIBRATION N.I.S.T. Traceable
	SERIAL NUMBER: <u>14772</u>
	CALIBRATION FACTOR: <u>1020 G/v</u>
	DATE: <u>11-July-12</u>
PDA OPERATOR: <u>[Signature]</u>	←-AT:PIEZORESISTIVE OP: alex [ver:4.05]

←-AT:PIEZORESISTIVE