

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 05-Jan-15 05:33 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30 DL -41 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1015	FS — BN 2044 PJ: 10 SL 587/ 3440/ 99 PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 14773-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 VE 1022 LI 1.0
---	--

ACCEPT SQ-OFF FL-OFF PR-OFF contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.3 FMX= 66 AMX= 139 EMX= 0.3 MEX= 129 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>14773</u> CALIBRATION FACTOR: <u>1015%</u> PAK ←*5000→: _____ DATE: <u>5 JAN 15</u> PDA OPERATOR: <u>M. Wray</u> OP: laine [ver:4.05]
--	---

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->