

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 28-Jun-05 11:05	FS — 10	BN 379 SL 2533/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -39 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1020						
TS 12 TB 8.0					B PD: 14776-060 T1 9.6 2L/C 4.7 VA 200	LP 0.00 ft LI 1.0
UMX= 4.6 FMX= 73 AMX= 179 EMX= 0.3 MEX= 143 FVP= 1.01						
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 14776 CALIBRATION FACTOR: 1020 G/V						
PAK (*5000): _____ DATE: 28-Jun-05 PDA OPERATOR: <i>Fred Iver</i>						

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 14776
 CALIBRATION FACTOR: 1020 G/V
 PAK (*5000): _____ DATE: 28-Jun-05
 PDA OPERATOR: *Fred Iver*

<-AT:PIEZORESISTIVE

OP: FRED Iver:4.051

AT:PIEZOELECTRIC->