

QBTA: DN [ALT-F1/BB=601

Pile Dynamics, Inc.

DPF

Pile Dynamics 04-Oct-16 04:32	FS — 10	BN 594 SL 613/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN <del>KIPS</del> 30.1 FR 20000 MB 30	TS 12 B PD: 15062-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
DL -39 UT -1 PK 1 TM-PEAK	F1 500 F2 213 A1 999 A2 1000			

ACCEPT SQ-OFF FL-OFF PR-OFF	VMX= 4.5 FMX= 70 AMX= 149 EMX= 0.3 MEX= 137 FVP= 1.00
<p>contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 15062 CALIBRATION FACTOR: 1000 g/v PAK (*5000): DATE: 5 OCT 16 PDA OPERATOR: <i>[Signature]</i>

<-AT:PIEZORESISTIVE

OP: Iaine Iver:4.051

AT:PIEZOELECTRIC->