

File Dynamics 11-Jan-12 11:47 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 MS 16810 ft/s MC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS FR 20000 MB 30 DL -34 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1020	FS — BN 856 PJ: sn 10 SL 3276/ 3440/ 99 PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 15994-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0
--	--

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 3.9 FMX= 61 AMX= 139
 EMX= 0.2 MEX= 119 FVP= 1.00



contact File Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 15994
 CALIBRATION FACTOR: 1020 G/v
 PAK (*5000): DATE: 11-JAN-12
 PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->