

Pile Dynamics 19-Oct-05 08:56 FS — BN 679 SL 2552/ 3440/ 99 PN: HOBBAR PJ: PJ: HOBBAR TG F2 -- US H2 F2 3.3		DBTA: ON IALT-F1/BB=60 Pile Dynamics, Inc. DPF	
LE 39.6 ft RH 1.7 in2 EM 30000 KSI SP 0.492 K/ft3 MS 16810 ft/s MC 16862 ft/s JC 0.40 FM 1.00 VM 1.00		EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK FT 500 F2 213 A1 999 A2 1068	
TS 12 B PDI: 16189-60 TI 9.4 2L/C 4.7 VA 200 LP 0.00 ft LI 1.0 VE 1022		UMX = 3.6 FMX = 56 AMX = 110 EMX = 0.2 MEX = 109 FVP = 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable	
SERIAL NUMBER: 16189 CALIBRATION FACTOR: 1068 611 DATE: 19 Oct 05 PDA OPERATOR: <i>AKC</i> PAK (*50007)		contact Pile Dynamics USA with your questions tel USA - 216 - 831-6131 fax USA - 216 - 831-0916 <-AT:PIEZORESISTIVE OP: FRED Lvar:4.050 <-AT:PIEZOELECTRIC->	

