

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 22-Sep-05 10:15		FS — 10	BN 320 SL 2499/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1027	TS 12 TB 7.0	E B T1 9.5	PD: 16207-060 2L/C 4.7 VA 1000	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF	VMX= 4.3 FMX= 66 AMX= 149 EMX= 0.3 MEX= 129 FVP= 0.99
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 16207 CALIBRATION FACTOR: 1027 G/V PAK (X5000): _____ DATE: 22-Sep-05 PDA OPERATOR: <i>Fred Hein</i>
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	OP: FRED [ver:4.05]

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->