


QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

| | |
|--|--|
| Pile Dynamics 11-Oct-05 09:19 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -45 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 995 | FS — BN 357 PJ: 10 SL 2511/ 3440/ 99 PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 16210-060 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 VE 1022 LI 1.0 |
|--|--|

| | |
|---|--|
| ACCEPT SQ-OFF FL-OFF PR-OFF  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916 | VMX= 5.4 FMX= 84 AMX= 219 EMX= 0.4 MEX= 164 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>16210</u> CALIBRATION FACTOR: <u>995 G/V</u> PAK (*5000): _____ DATE: <u>11-Oct-05</u> PDA OPERATOR: <u>Fred Han</u> |
|---|--|

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->