

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 03-May-17 21:14	FS — 10	BN 129 SL 417/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3				
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s								
JC 0.40 FM 1.00 VM 1.00								
EA/C 30.3 Ks/ft UN KIPSS0.1 FR 20000 MB 30								
DL -39 UT -1 PK 1 TM-PEAK								
F1 500 F2 213 A1 999 A2 1000								
TS 12 TB 8.0					B PD: 16218-060 T1 9.5 2L/C 4.7	VA 1000	VE 1022	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF								
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916								
<-AT:PIEZORESISTIVE OP: laine [ver:4.05] AT:PIEZOELECTRIC->								

VMX= 4.5 FMX= 71 AMX= 139
 EMX= 0.3 MEX= 139 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 16218

CALIBRATION FACTOR: 1000 g/v

PAK (*5000): DATE: 4 MAY 17

PDA OPERATOR: [Signature]