

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

<b>Pile Dynamics</b> 12-Jul-07 11:57 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN <del>KIPS</del> 0.1 FR 20000 MB 30  DL -31 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1030	FS — 10	BN 218 SL 2690/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
---	------------	-----------------------------	----------------------	--------------------------

  

TS 12	B PD: 16223-060	LP 0.00 ft	
TB 8.0	T1 9.5 2L/C 4.7 VA 1000	UE 1022 LI 1.0	

<b>ACCEPT SQ-OFF FL-OFF PR-OFF</b>   contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 3.8 FMX= 59 AMX= 129 EMX= 0.2 MEX= 115 FUP= 0.99  ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>16223</u> CALIBRATION FACTOR: <u>1030 6V</u> RAK <del>(5000)</del> : _____ DATE: <u>12-JUL-07</u> PDA OPERATOR: <u>[Signature]</u>
--	---

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->