

Pile Dynamics 09-May-12 08:18 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 MS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS 0.0 FR 20000 MB 3D DL -28 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1040	FS 10 BN 190 SL 3211/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 TB 8.0 B PD: 16231-060 T1 9.5 2L/C 4.7 UA 1000 LP 0.00 ft LI 1.0
---	---

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.0 FMX= 61 AMX= 159
 EMX= 0.2 MEX= 119 FUP= 0.99



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 16231
 CALIBRATION FACTOR: 1040 G/v
 PAK (*5000): DATE: 09-MAY-12
 PDA OPERATOR: *[Signature]*

File Dynamics 09-May-12 08:13 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16510 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS=0.1 FR 5000 MB 30 DL -24 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1040	FS 15 BN 176 SL 3211/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 4.9 TS 200 B PD: 16231-060 LP 0.00 ft TB 0.0 T1 15.8 2L/C 4.8 UA 1000 VE 1022 LI 1.0
---	---

VMX= 7.0 FMX= 106 AMX= 284
 EMX= 0.7 MEX= 207 FUP= 1.02

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: _____
 CALIBRATION FACTOR: _____
 PAK (*5000): _____ DATE: _____
 PDA OPERATOR: _____

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

>AT:PIEZOELECTRIC->