

Pile Dynamics 02-Jul-13 12:53		FS — 10	BN 244 SL 124/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 NS 16810 ft/s WC 17043 ft/s								
JC 0.40 FM 1.00 UM 1.00								
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 3D								
DL -38 UT -1 PK 1 TM-PEAK								
F1 500 F2 213 A1 999 A2 1145								
TS 12 TB 8.0						B PD: 44653 T1 9.3 2L/C 4.7	UA 1000 UE 1022	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF								
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916								
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>44653</u> CALIBRATION FACTOR: <u>1145 G/Y</u> PAK (*5000): _____ DATE: <u>2 Jul 13</u> PDA OPERATOR: <u>[Signature]</u>								

UMX= 2.7 FMX= 42 AMX= 80
 EMX= 0.2 MEX= 82 FUP= 1.00
 <-AT:PIEZORESISTIVE OP: dale [ver:4051] AT:PIEZOELECTRIC->